


856883

737 MHz SAW Filter

Applications

- General purpose wireless
- Wireless infrastructure
- 3G, 4G, Multi-standard
- Repeaters



Product Features

- Usable bandwidth 18 MHz
- High attenuation
- Low Loss
- Excellent power handling
- Single-ended operation
- No matching required for operation at 50Ω
- Small Size: 3.00 x 3.00 x 1.22 mm
- Ceramic Surface Mount Package (SMP)
- Hermetically Sealed
- **RoHS** compliant, **Pb**-free


General Description

856883 is a general purpose Downlink filter for band 12. This filter was specifically designed in a 3x3mm hermetic package for base station applications and is part of our wide portfolio of RF filters in the same package.

Low insertion loss, coupled with high attenuation and excellent power handling, makes this filter a natural choice for our customers Downlink RF filtering needs.

Functional Block Diagram

Top view



Pin Configuration

Pin #	Balanced	Description
2		Input
5		Output
1,3,4,6		Case Ground

Ordering Information

Part No.	Description
856883	packaged part
856883-EVB	evaluation board

Standard T/R size = 5000 units/reel.

Specifications

Electrical Specifications ⁽¹⁾

Specified Temperature Range: ⁽²⁾ -40 to +85 °C

Parameter ⁽³⁾	Conditions	Min	Typical ⁽⁴⁾	Max	Units
Center Frequency		-	737	-	MHz
Maximum Insertion Loss	728 – 746 MHz	-	1.8	2.25	dB
Lower 3 dB Band Edge ⁽⁵⁾		-	722.3	728	MHz
Upper 3 dB Band Edge ⁽⁵⁾		746	751.8	-	MHz
Absolute Attenuation ⁽⁵⁾	10 – 700 MHz	40	50	-	dB
	700 – 708 MHz	37	46	-	dB
	766 – 1500 MHz	40	43	-	dB
	1500 – 2000 MHz	30	35	-	dB
Input Return Loss	728 – 746 MHz	10	12.5	-	dB
Output Return Loss	728 – 746 MHz	10	12.5	-	dB
Source Impedance ⁽⁶⁾	Single-ended	-	50	-	Ω
Load Impedance ⁽⁶⁾	Single-ended	-	50	-	Ω

Notes:

1. All specifications are based on the TriQuint schematic for the main reference design shown on page 3
2. In production, devices will be tested at room temperature to a guardbanded specification to ensure electrical compliance over temperature
3. Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances
4. Typical values are based on average measurements at room temperature
5. Relative to zero dB
6. This is the optimum impedance in order to achieve the performance shown


Absolute Maximum Ratings

Parameter	Rating
Operating Temperature	-40 to +85 °C
Storage Temperature	-40 to +85 °C
Input Power ⁽⁷⁾	+20 dBm

7. Input Power is targeted for an applied CW modulated RF in the 728-746 MHz band at 55 °C for a minimum of 10000 hrs
Operation of this device outside the parameter ranges given above may cause permanent damage.

Reference Design


Schematic



Notes:

1. Actual matching values may vary due to PCB layout and parasitic


PC Board



Notes:

Top, middle & bottom layers: 1 oz copper
Substrates: FR4 dielectric, .031" thick
Finish plating: Nickel: 3-8 μ m thick, Gold: .03-.2 μ m thick
Hole plating: Copper min .0008 μ m thick

Mounting Configuration



Notes:

1. All dimensions are in millimeters.
2. This footprint represents a recommendation only.





Bill of Material

Reference Desg.	Value	Description	Manufacturer	Part Number
SMA	N/A	SMA connector	Radiall USA Inc.	9602-1111-018
PCB	N/A	3-layer	multiple	960700


856883

737 MHz SAW Filter


Typical Performance (at room temperature)



Input Smith Chart



Output Smith Chart




856883

737 MHz SAW Filter

Mechanical Information

Package Information, Dimensions and Marking



Package Style: SMP-12A
Dimensions: 3.00 x 3.00 x 1.22 mm



Body: Al_2O_3 ceramic
Lid: Kovar, Ni plated
Terminations: Au plating 0.5 - 1.0 μ m, over a 2-6 μ m Ni plating

All dimensions shown are nominal in millimeters
All tolerances are ± 0.15 mm except overall length and width ± 0.10 mm

The date code consists of: day of the current year (Julian, 3 digits), Y = last digit of the year, and M = manufacturing site code

Tape and Reel Information

Standard T/R size = 5000 units/reel. All dimensions are in millimeters



Product Compliance Information

ESD Information



Caution! ESD-Sensitive Device

ESD Rating: 0

Value: Passes ≥ 200 V min.
Test: Human Body Model (HBM)
Standard: JEDEC Standard JESD22-A114

ESD Rating: A

Value: Passes ≥ 200 V min.
Test: Machine Model (MM)
Standard: JEDEC Standard JESD22-A115

MSL Rating

Devices are Hermetic, therefore MSL is not applicable

Solderability

Compatible with the latest version of J-STD-020, lead free solder, 260°C

Refer to [Soldering Profile](#) for recommended guidelines.

This part is compliant with EU 2002/95/EC RoHS directive (Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment).

This product also has the following attributes:

- Halogen Free (Chlorine, Bromine)
- Antimony Free
- TBBP-A ($C_{15}H_{12}Br_4O_2$) Free
- PFOS Free
- SVHC Free

Contact Information

For the latest specifications, additional product information, worldwide sales and distribution locations, and information about TriQuint:

Web: www.triquint.com
Email: info-sales@tqs.com

Tel: +1.407.886.8860
Fax: +1.407.886.7061

For technical questions and application information:

Email: flapplication.engineering@tqs.com

Important Notice

The information contained herein is believed to be reliable. TriQuint makes no warranties regarding the information contained herein. TriQuint assumes no responsibility or liability whatsoever for any of the information contained herein. TriQuint assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for TriQuint products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

TriQuint products are not warranted or authorized for use as critical components in medical, life-saving, or life-sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.