Gore Cable Assembly Builder

Microwave Assembly Part Number 2Z0AJ0AK0240

W. L. Gore & Associates has developed and proven a wide range of products specifically tailored to the RF / microwave industry. Since 1976, when Gore first introduced our microwave assemblies, Gore has remained a worldwide leader in providing custom microwave assemblies for demanding applications. Typical applications using GORE & Microwave Assemblies include: test, aerospace, defense, telecommunications and general purpose. With an unmatched history in demanding environments, you may be assured that Gore will provide the reliable products necessary to meet your individual system requirements.

GORE™ Microwave Assemblies provide superior insertion loss, phase stability, and shielding effectiveness. These assemblies offer proven solutions for your low loss, high density, wide bandwidth or high power applications. Gore offers a variety of standard cable and connector options to satisfy the needs of most RF applications from DC to 67 GHz. Applications using these high performance interconnects vary from general purpose lab to military installations on airborne, naval, and land platform

PFA Outer Jacket Inner Braid Outer Conductor GORE™ ePTFE Dielectric Center Conductor

Specifications

opoomoutiono	
Max Frequency GHz	50
Impedance Ohms	50
Center Conductor	Solid
Dielectric Constant (nominal)	1.4
Velocity of Propagation	0.85
Temperature °C	-55 to 75
Nominal Outer Diameter in. (mm)	0.140 (3.6)
Minimum Bend Radius (multiple bends) in. (mm)	1 (25.4)
Nominal Weight g/ft (g/m)	9 (29.5)
Crush Resistance lb/linear in.	50
Typical Insertion Loss dB at 50 GHz	-2.5375
Guaranteed Insertion Loss dB at 50 GHz	-3.4948
Guaranteed VSWR at 50 GHz	1.42:1
Guaranteed Return Loss dB	-15.28


Key Features

- Optimized electrical performance
- High-frequency options (up to 67 GHz)


Key Benefits

- Increased signal fidelity Easy to route/install
- Broad bandwidth capability

Typical Insertion Loss




Guaranteed Insertion Loss




Connector A

Type: Straight, Family: 2.4 mm, Sex: Pin (Plug)



Connector B

Type: Straight, Family: 2.4 mm, Sex: Socket (Jack)



Phone (In USA): 1-800-445-GORE (800-445-4673) Phone (outside the US): +1/302-292-5100 The data in this datasheet applies to standard GORE & Microwave / RF Cable Assemblies and performance may vary based on specific application conditions.